



021 088 97399
sales@aescomp.co.nz

Installation Contactors 4P 25Amps 2M

EPC1-25-40 / EPC1-25-22 / EPC1-25-31 / EPC1-25-04


MAXGE



Features

- IEC/EN61095
- IEC/EN60947-4-1
- Ie 25A
- Ue~ 400V
- Ui~ 500V
- AC-7a 25A
- AC-7b 9A
- Flame retardent body
- Operating status window
- Latching DIN rail clip
- Side mount auxiliary contacts
- IP20 touchproof terminals
- 3 Years (return to supplier) warranty

Dimensions



Description

- Modular Installation Contactor - two modules width (36mm wide). Either 24 or 230VAC 50/60Hz control.

Model	Description	Contacts
EPC1-25-40-24 / EPC1-25-40-230	Modular Installation Contactor	4NO
EPC1-25-22-230	Modular Installation Contactor	2NO + 2NC
EPC1-25-31-230	24V or 230V 50/60Hz	3NO + 1NC
EPC1-25-04-230	(select model and voltage)	4NC
EPC1-MA	Auxiliary Contact - Side Mount	1NO+1NC 5Amps 230VAC/1Amp 130VDC

Characteristics

Terminal Capacity	Coil Main	0.75-2.5mm ² 1.5-6mm ²
Terminal Torque		0.8-3.5Nm
Endurance (Op's)	Electrical Mechanical	100,000 5,000,000
Operating Temperature		-5 ~ +60°C
Humidity (max.)		95%

Safety Precautions

- ✦ The device must be installed by a qualified person
- ✦ Disconnect all power before working on the device
- ✦ Don't touch any of the terminals when the power is on
- ✦ Verify correct terminal connection when wiring
- ✦ Do not dismantle or repair the device otherwise no responsibility is assumed by the manufacturer, or AES Components Ltd
- ✦ This device must be mounted in an appropriately rated enclosure, distribution board or switchboard for the environment
- ✦ The device can be cleaned with a dry cloth
- ✦ Failure to follow these instructions may result in serious injury




Product Features



EPC1 Modular Contactors
AC-7a: 25 / 40 / 63Amps
2 Pole: 2NO / 1NO+1NC / 2NC
4 Pole: 4NO / 4NC / 2NO+2NC / 3NO+1NC

Operating Status Indication



Clear Ratings



Side Mount Auxiliary Contact Accessories



Latchable DIN Rail Clip

