



021 088 97399  
sales@aescomp.co.nz

## Changeover Switches 63A

**MG-MCS-1P-63 / MG-MCS-2P-63**  
**MG-MCS-3P-63 / MG-MCS-4P-63**

**MAXGE**



### Features

- IEC/EN60947-3
- $I_e$  63A
- $U_e$  1P 230V
- $U_e$  2P+ 415V
- Changeover switch with centre off
- Clear switch position I - 0 - II
- Flame retardent body
- IP20 touchproof terminals
- Warranty 3 Years (return to supplier)

### Switching

	I	0	II
	Connected		Connected
	1 & 2	All positions disconnected	1 & 4
	5 & 6		5 & 8
	9 & 10		9 & 12
	13 & 14		13 & 16

### Description

- Modular changeover switch with centre off 63 Amps, 1 pole / 2 pole / 3 pole / 4 pole

MG-MCS-1P-63  
MG-MCS-2P-63  
MG-MCS-3P-63  
MG-MCS-4P-63

Modular change over switch  
230 / 415V

1 Pole 1 x 18mm Module  
2 Pole 2 x 18mm Modules  
3 Pole 3 x 18mm Modules  
4 Pole 4 x 18mm Modules

### Characteristics

Terminal Capacity	16mm <sup>2</sup>
Terminal Torque	Nm
Endurance Electrical	1,500
(Op's) Mechanical	8,500
Operating Temperature	-5 ~ +40°C

### Safety Precautions

- ✦ The device must be installed by a qualified person
- ✦ Disconnect all power before working on the device
- ✦ Don't touch any of the terminals when the power is on
- ✦ Verify correct terminal connection when wiring
- ✦ Do not dismantle or repair the device otherwise no responsibility is assumed by the manufacturer, or AES Components Ltd



- ✦ This device must be mounted in an appropriately rated enclosure, distribution board or switchboard for the environment
- ✦ The device can be cleaned with a dry cloth
- ✦ Failure to follow these instructions may result in serious injury


### Range Overview

MG-MCS-1P-63A




1M 18mm Width

MG-MCS-2P-63A




2M 36mm Width

MG-MCS-3P-63A



3M 54mm Width

MG-MCS-4P-63A



4M 72mm Width